

---



---

**Specifications<sup>(A)</sup>**  
**BRAVO 68 MOTOR YACHT**

Length Overall	69' 0"	21.03m
Length Waterline	61' 9"	18.82m
Beam	18' 11"	5.77m
Draft	5' 5"	1.65m
Displacement (full load – est.)	101,000 lbs	46,000 kg
Fuel <sup>(B)</sup>	1,600 USG	6,060 ltr
Water <sup>(B)</sup>	430 USG	1,630 ltr
Gray Water <sup>(B)</sup>	150 USG	570 ltr
Black Water <sup>(B)</sup>	150 USG	570 ltr
Engines	Twin CATERPILLAR C18 ACERT (1,136 bhp each)	
Generator	KOHLER 32 kW, 60Hz	
Naval Architect <sup>(C)</sup>	Tom Fexas Yacht Design	

---

**STANDARD EQUIPMENT**

---

**Construction**

- Hull, deck, superstructure, bulkheads and cabin soles, vinylester resin infused multi-axial E-glass reinforced foam cored fiberglass
- Integral fiberglass fuel, fresh water and holding tanks, with baffles and manholes
- Epoxy hull barrier with five-year structure and osmosis warranty
- *Sunbrella* upholstered Dryfast exterior seating
- Honeycomb cored cabinetry and partitions

---

**Equipment**

- BUELL twin trumpet air horn
- Fresh water anchor wash down
- Emergency lighting system operating from an independent power supply
- Under water main engine exhausts
- CENTEK air/water separator generator mufflers
- 220vAC reverse cycle direct expansion air-conditioning
- Manual/automatic fire extinguishing system with alarms, blower shut down and vent closure
- Demisters on air intakes
- REVERSO lube oil change system for engines, generators and gearboxes
- NAIAD 7.5 sq. ft stabilizers and Multisea dual station control
- SIDE-POWER 12", 16hp DC bow thruster
- MATHERS MC2000-2 electronic engine controls
- STIDD helm seats for pilothouse and flybridge
- MAXWELL VWC 3500 windlass, 30 fathoms 3/8" high test chain
- 66 lb. (30 kg) BRUCE anchor
- NAUTICAL STRUCTURES 1,500lb davit

- ACR 100 searchlight with dual station remote control
- SEASHAFT 22 or equal propeller shafts
- Nibral propellers, 4 blade, class S, dynamically balanced
- PYI packless shaft seals
- HEADHUNTER electric WC's for guest heads, fresh water flush
- GLENDINNING Cablemaster shore power cable retrieval system, 230v/100A with 100ft. cable
- Isolation transformer (25 kVA) for shore power system
- LCD touch screen control/alarm/monitoring PLC with audible and visual signals
- Security alarm on all doors and hatches
- Engine driven emergency bilge pump
- HART Tank Tender gauges
- Galley appliances;
  - range/oven unit
  - microwave oven with ventilation hood
  - refrigerator/freezer with ice dispenser
  - dishwasher
  - garbage disposal
- 24" stack up washer/dryer